

**Internal micrometers, 2-point XTA MICRO in box  
including setting ring and UKAS calibration certificate  
2-2,5/0,001/9mm**

|                             |                         |
|-----------------------------|-------------------------|
| <b>Product number:</b>      | 2094096                 |
| <b>EAN / GTIN:</b>          | 5051102212254           |
| <b>Manufacturer number:</b> | MXTA1M                  |
| <b>Customs code:</b>        | 90173000                |
| <b>Delivery method:</b>     | Parcel delivery service |
| <b>Weight:</b>              | 0.5kg                   |



## Product description

- DIN 863
- Satin chrome reading parts
- For measuring ranges < 20mm XTA MICRO will be delivered
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Spindle pitch 0.5mm
- Sturdy ratchet

**Delivered in a case, including setting ring and UKAS calibration certificate**

## Technical Data

|                             |                     |
|-----------------------------|---------------------|
| <b>Size:</b>                | 2-2,5/0,001/9mm     |
| <b>Article number:</b>      | 2094096             |
| <b>Brand:</b>               | BOWERS              |
| <b>Manufacturer number:</b> | MXTA1M              |
| <b>Accuracy:</b>            | 0,004mm             |
| <b>Measuring depth:</b>     | 9mm                 |
| <b>Measuring force:</b>     | 18-12N              |
| <b>Measuring range:</b>     | 2-2,5mm             |
| <b>Reading:</b>             | 0,001mm             |
| <b>Reading parts:</b>       | Satin chrome plated |
| <b>Setting ring:</b>        | With                |
| <b>Setting ring:</b>        | Ø 2,5mm             |
| <b>Spindle pitch:</b>       | 0,5mm               |
| <b>Weight:</b>              | 0.5kg               |