

Digital wall thickness testers ULTRA active in box incl. external measuring head and calibration plate 1,2 ... 225 / 0,1mm IP54

Product 2149905

number:

EAN / 4066918088314

GTIN:

Customs 90318080

code:

Delivery Parcel delivery service

method:

Weight: 0.16kg



Product description

- Protection class IP54
- LCD display
- Commutation mm / inch
- Test head with 1m cable
- Accuracy: $\pm 0.5\%$ of the measured value
- Ultrasonic pulse echo technique
- Range of sound velocity 500 to 9000 m/s
- Frequency range 5 MHz, test head $\varnothing$ 8mm
- Surface temperature: $-15^{\circ}\text{C} \dots +60^{\circ}\text{C}$
- Dust and water proof housing
- Data output RS232

**Delivered in a box incl. probe, zero standard and batteries

Application:

- Used for measuring thickness corrosion of pressure vessels, chemical equipment, boiler, oil storage tanks, pipes etc.

Materials:

- Any hard material, like steel, cast iron, aluminium, red copper, brass, zinc, quartz glass, polyethylene, PVC, homogeneous plastics etc.

Technical Data

Size: 1,2 ... 225 / 0,1mm IP54

Article no.: 2149905

Brand: ULTRA

Dimension: 120x62x30mm

Weight: 0.16kg