

## Limit plug gauges DIN2245 Express

(Go + NoGo)

Ø 3,001-6,000/0,001mm

**Product** 1081302ex  
**number:**

**EAN /** 4066918009432

**GTIN:**

**Customs** 90318020

**code:**

**Delivery** Parcel delivery service

**method:**

**Weight:** 0.03kg



### Product description

- DIN 2245 until Ø 65.000mm (GO and NO-GO sides on one gauge)
- DIN 2246 / 2247 > Ø 65.000mm (Separate GO and NO-GO sides, pair)
- ISO Tolerance A-ZC, Qualities >= 6, all intermediate dimensions, all numerical tolerances up to and including tolerance quality IT6
- GO and NO-GO side, Hardened tool steel
- GO side with wear allowance (workshop gauge)

#### Delivered in individual packages

**1081 2..zm:** Regular delivery time

**1081 3..ex :** Express Service, ULTRA fast delivery

**! Order notice - Please enter exact nominal diameter, e.g. Ø 7.58mm or Ø 20.495mm, as well as the required tolerance e.g. H6 or 0/+0.05mm**

**! Measuring faces + handles in special shape, master gauges and larger lengths not possible in fast service.**

**! TIN- and TICN-coated limit plug gauges, master gauges without wear allowance and measuring faces in special shapes on request.**

**Diamond Graphite coating for limit plug gauges from Ø 3mm on request. Advantages: Longer service life, corrosion resistant, low friction and wear resistant. This coating is not possible for master gauges.**

## Technical Data

|                         |                       |
|-------------------------|-----------------------|
| <b>Size:</b>            | Ø 3,001-6,000/0,001mm |
| <b>Article no.:</b>     | 1081302ex             |
| <b>Brand:</b>           | ULTRA                 |
| <b>Express service:</b> | YES                   |
| <b>Material:</b>        | Hardened steel        |
| <b>Nominal size:</b>    | Ø 3,001-6,000mm       |
| <b>Step:</b>            | 0,001mm               |
| <b>Weight:</b>          | 0.03kg                |