

## Digital hand lever bore gauges 3-point XTL in box including setting ring and UKAS calibration certificate 20-25/0,001/66mm

**Product number:** 2504206

**number:**

**EAN / GTIN:** 5051102123802

**Manufacturer** XTL20M

**number:**

**Customs code:** 90173000

**code:**

**Delivery method:** Parcel delivery service

**method:**

**Weight:** 1.93kg



### Product description

- DIN 863
- Excellent for vertical bore measurement
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Blind bore measurement from 12.5mm
- Movable measuring jaws through hand lever
- Constant measuring force, spring loaded
- Sylvac System, large LCD display
- Self-centering measuring heads for good positive feel

**Delivered in a case, including dial gauge, measuring head, setting ring gauge and UKAS calibration certificate**

#### Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function ±
- Max. / min. memory
- Hold function
- Data output Proximity

**! Measuring ranges > 100mm, depth extensions and measuring heads with special measuring faces (threads, grooves, spherical, serrations, 2-point etc.), digital dial indicators IP65 and digital dial indicators with bluetooth function for bore gauges > 20mm on request.**

## Technical Data

**Size:** 20-25/0,001/66mm

**Article no.:** 2504206

**Brand:** BOWERS

**Manufacturer number:** XTL20M

**Accuracy:** 0,004mm

**Data output:** Proximity

**Measuring depth:** 66mm

**Measuring force:** 35-15N

**Measuring range:** 20-25mm/.8-1 inch

**Reading:** 0,001mm/.00005 inch

**Setting ring:** Ø 20mm

**Size A:** 0,5mm

**Weight:** 1.93kg