

## Digital hand lever bore gauge sets 3-point XTL in box including setting rings and UKAS calibration certificate 20-50/0,001/66/80mm

<b>Product number:</b>	2504503
<b>EAN / GTIN:</b>	5051102120542
<b>Manufacturer number:</b>	SXTL5M
<b>Customs code:</b>	90173000
<b>Delivery method:</b>	Parcel delivery service
<b>Weight:</b>	3.43kg



### Product description

- DIN 863
- Excellent for vertical bore measurement
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Blind bore measurement from 12.5mm
- Movable measuring jaws through hand lever
- Constant measuring force, spring loaded
- Sylvac System, large LCD display
- Without Bluetooth function
- Self-centering measuring heads for good positive feel

**Delivered in a case, including dial gauge, measuring heads, setting rings and UKAS calibration certificate**

#### Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function  $\pm$
- Max. / min. memory
- Hold function
- Data output Opto

#### Contents:

- 1 piece Digital readout unit with dial gauge
- 2 pieces measuring heads (1 piece of each measuring range 6-8 / 8-10mm)
- 1 piece setting ring Ø 8mm

**! Measuring ranges > 100mm, depth extensions and measuring heads with special measuring faces (threads, grooves, spherical, serrations, 2-point etc.), digital dial indicators IP65 and digital dial indicators with bluetooth function for bore gauges > 20mm on [request](#).**

## Technical Data

<b>Size:</b>	20-50/0,001/66/80mm
<b>Article no.:</b>	2504503
<b>Brand:</b>	BOWERS
<b>Manufacturer number:</b>	SXTL5M
<b>Accuracy:</b>	0,004mm
<b>Data output:</b>	Proximity
<b>Measuring depths:</b>	66/80mm
<b>Measuring force:</b>	35-15N
<b>Measuring range:</b>	20-50mm/.8-2 inch
<b>Number of measuring heads:</b>	3
<b>Reading:</b>	0,001mm/.00005 inch
<b>Setting rings:</b>	Ø 20/35mm
<b>Size A:</b>	0,5mm
<b>Weight:</b>	3.43kg