

Digital dial test indicators (lever type) S_Dial TEST Smart Bluetooth

0,8/0,001/12,5mm Ø45mm IP54

Product number: 1339601

EAN / GTIN: 4066918047557

Manufacturer number: 805.4321

Customs code: 90178090

Delivery method: Parcel delivery service

Weight: 0.07kg



Product description

- Works standard
- Protection class IP54
- LCD display, analogue/digital, turnable 270°
- With Bluetooth function for a wireless data transmission
- Repeatability 0.001mm
- Outer ring Ø 45mm
- Clamping shaft Ø 8mm h6
- Dovetail slide x 3
- Probe swivelling through 270°, tungsten carbide ball Ø 2mm, M 1.4

Delivered in a cardboard box including manufacturer certificate. Simply scan the QR code on the housing, go to Calibration certificate and save.

Functions:

- On/Off
- Auto-Off
- mm/inch commutation
- Reversible reading 0.01 / 0.001mm
- Zero setting at any position
- ABS function
- Hold function
- $\pm$ Preset function
- MIN. / MAX. / DELTA. memory
- Conversion factor
- Reversible measuring direction
- Key lock
- Data output Proximity

Technical Data

Size:	0,8/0,001/12,5mm Ø45mm IP54
Article no.:	1339601
Brand:	SYLVAC
Manufacturer number:	805.4321
Bluetooth:	With
Error max.:	0,004mm
Measuring force:	0,15N
Measuring range:	0,8mm
Number of probes:	1
Probe length:	12,5mm
Reading:	0,001mm
Weight:	0.07kg