

Digital pistol grip bore gauge sets, 3-point XT GROOVE for groove meas., incl. setting rings & UKAS calibration 6-20/0,001/58/62mm Bluetooth

Product 2510607b

number:

Manufacturer SP-SXTH10M-BT-GRO

number:

Customs 90173000

code:

Delivery Parcel delivery service

method:

Weight: 2.7kg



Product description

- DIN 863
- Protection class IP67, Sylvac System
- Stepped hardened steel measuring faces
- Minimum entry-Ø for groove profile: 0.3mm below minimum
- When used with a depth stop, the groove heads can be used to measure plain bores as well as grooves
- Pistol handle
- Large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Constant measuring force, spring loaded

Delivered in a case, including setting rings, UKAS calibration certificate and depth stops

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function ±
- Max. / min. memory
- Hold function
- Data output Proximity

Contents:

- 1 piece Digital readout unit with pistol grip
- 5 pieces measuring heads (1 piece of each measuring range 6-8 / 8-10 / 10-12.5 / 12.5-16 / 16-20mm)
- 3 pieces setting rings (1 piece of each Ø 8 / 12.5 / 20mm)

! Digital pistol grip bore gauges XT GROOVE for measuring special groove profiles, single devices, tungsten carbide-tipped measuring faces and extensions on request.

! Please specify the dimensions according to the sketch viewable above. This data is required to enable us to prepare a quotation. Alternatively, you can also send us a workpiece drawing.

Technical Data

Size: 6-20/0,001/58/62mm Bluetooth

Article no.: 2510607b

Brand: BOWERS

Manufacturer number: SP-SXTH10M-BT-GRO

Accuracy: 0,004mm

Depth stops: Ø 18/20/22/26/33mm

For groove depths: 1,25/1,5/2/2,5mm

For groove width: 1,5mm

Measuring depths: 58/62mm

Measuring force: 18-8N

Measuring range: 6-20mm/.25-.8 inch

Reading: 0,001mm/.00005 inch

Setting rings: Ø 8/12,5/20mm

Weight: 2.7kg