

**Digital hand lever bore gauge sets 3-point XTL in box
including setting rings and UKAS calibration certificate
6-10/0,001/58mm Bluetooth**

Product 2504501b

number:

EAN / GTIN: 5051102251505

Manufacturer SXTL3M-BT

number:

Customs 90173000

code:

Delivery Parcel delivery service

method:

Weight: 2.28kg



Product description

- DIN 863
- Protection class IP67, Sylvac System
- Excellent for vertical bore measurement
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Blind bore measurement from 12.5mm
- Movable measuring jaws through hand lever
- Constant measuring force, spring loaded
- Sylvac System, large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Self-centering measuring heads for good positive feel

Delivered in a case, including dial gauge, measuring heads, setting rings and UKAS calibration certificate

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function \pm
- Max. / min. memory
- Hold function
- Data output Proximity

Contents:

- 1 piece Digital readout unit with dial gauge
- 2 pieces measuring heads (1 piece of each measuring range 6-8 / 8-10mm)
- 1 piece setting ring Ø 8mm

! Measuring ranges > 100mm, depth extensions and measuring heads with special measuring faces (threads, grooves, spherical, serrations, 2-point etc.), digital dial indicators IP65 and digital dial indicators with bluetooth function for bore gauges > 20mm on request.

Technical Data

Size: 6-10/0,001/58mm Bluetooth

Article no.: 2504501b

Brand: BOWERS

Manufacturer number: SXTL3M-BT

Accuracy: 0,004mm

Data output: Proximity

Measuring depths: 58mm

Measuring force: 18-8N

Measuring range: 6-10mm/.25-.4 inch

Number of measuring heads: 2

Reading: 0,001mm/.00005 inch

Setting rings: Ø 8mm

Size A: 1,6mm

Weight: 2.28kg