

**Digital hand lever bore gauge sets 3-point XTL in box  
including setting rings and UKAS calibration certificate  
10-20/0,001/58/62mm Bluetooth**

**Product number:** 2504502b  
**EAN / GTIN:** 5051102251512  
**Manufacturer number:** SXTL4M-BT  
**Customs code:** 90173000  
**Delivery method:** Parcel delivery service  
**Weight:** 2.65kg



## Product description

- DIN 863
- Protection class IP67, Sylvac System
- Excellent for vertical bore measurement
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Blind bore measurement from 12.5mm
- Movable measuring jaws through hand lever
- Constant measuring force, spring loaded
- Sylvac System, large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Self-centering measuring heads for good positive feel

**Delivered in a case, including dial gauge, measuring heads, setting rings and UKAS calibration certificate**

### Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function ±
- Max. / min. memory
- Hold function
- Data output Proximity

### Contents:

- 1 piece Digital readout unit with dial gauge
- 2 pieces measuring heads (1 piece of each measuring range 6-8 / 8-10mm)
- 1 piece setting ring Ø 8mm

**! Measuring ranges > 100mm, depth extensions and measuring heads with special measuring faces (threads, grooves, spherical, serrations, 2-point etc.), digital dial indicators IP65 and digital dial indicators with bluetooth function for bore gauges > 20mm on request.**

## Technical Data

<b>Size:</b>	10-20/0,001/58/62mm Bluetooth
<b>Article number:</b>	2504502b
<b>Brand:</b>	BOWERS
<b>Manufacturer number:</b>	SXTL4M-BT
<b>Accuracy:</b>	0,004mm
<b>Data output:</b>	Proximity
<b>Measuring depths:</b>	58/62mm
<b>Measuring force:</b>	18-8N
<b>Measuring range:</b>	10-20mm/.4-.8 inch
<b>Number of measuring heads:</b>	3
<b>Reading:</b>	0,001mm/.00005 inch
<b>Setting rings:</b>	Ø 12,5/20mm
<b>Size A:</b>	1,9/0,5mm
<b>Weight:</b>	2.65kg