

**Digital hand lever bore gauge sets 3-point XTL in box
including setting rings and UKAS calibration certificate
10-20/0,001/58/62mm Bluetooth**

Product number: 2504502b
EAN / GTIN: 5051102251512
Manufacturer number: SXTL4M-BT
Customs code: 90173000
Delivery method: Parcel delivery service
Weight: 2.65kg



Product description

- DIN 863
- Protection class IP67, Sylvac System
- Excellent for vertical bore measurement
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Blind bore measurement from 12.5mm
- Movable measuring jaws through hand lever
- Constant measuring force, spring loaded
- Sylvac System, large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Self-centering measuring heads for good positive feel

Delivered in a case, including dial gauge, measuring heads, setting rings and UKAS calibration certificate

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function \pm
- Max. / min. memory
- Hold function
- Data output Proximity

Contents:

- 1 piece Digital readout unit with dial gauge
- 2 pieces measuring heads (1 piece of each measuring range 6-8 / 8-10mm)
- 1 piece setting ring Ø 8mm

! Measuring ranges > 100mm, depth extensions and measuring heads with special measuring faces (threads, grooves, spherical, serrations, 2-point etc.), digital dial indicators IP65 and digital dial indicators with bluetooth function for bore gauges > 20mm on request.

Technical Data

| | |
|----------------------------|-------------------------------|
| Size: | 10-20/0,001/58/62mm Bluetooth |
| Article number: | 2504502b |
| Brand: | BOWERS |
| Manufacturer number: | SXTL4M-BT |
| Accuracy: | 0,004mm |
| Data output: | Proximity |
| Measuring depths: | 58/62mm |
| Measuring force: | 18-8N |
| Measuring range: | 10-20mm/.4-.8 inch |
| Number of measuring heads: | 3 |
| Reading: | 0,001mm/.00005 inch |
| Setting rings: | Ø 12,5/20mm |
| Size A: | 1,9/0,5mm |
| Weight: | 2.65kg |