

**Digital wall thickness testers ULTRA active in box
incl. external measuring head and calibration plate
3 ... 300 / 0,01mm IP54**

Product number: 2149908

EAN / GTIN: 4066918103932

Customs code: 90241040

Delivery method: Parcel delivery service

Weight: 0.25kg



Product description

- Protection class IP54
- LCD display
- Commutation mm / inch
- Test head with 0,9m cable
- Accuracy: ± 0.5 % of the measured value
- Ultrasonic pulse echo technique
- Range of sound velocity 1000 to 9999 m/s
- Frequency range 2,5 MHz, test head \varnothing 14mm
- Surface temperature: $-15^{\circ}\text{C} \dots + 60^{\circ}\text{C}$
- Dust and water proof housing
- Data output RS232

**Delivered in a box incl. probe, zero standard and batteries

Application:

- Used for measuring thickness corrosion of pressure vessels, chemical equipment, boiler, oil storage tanks, pipes etc.

Materials:

- Any hard material, like steel, cast iron, aluminium, red copper, brass, zinc, quartz glass, polyethylene, PVC, homogeneous plastics etc.

Technical Data

Size: 3 ... 300 / 0,01mm IP54

Article number: 2149908

Brand: ULTRA

Dimension: 150x74x32mm

Weight: 0.25kg