

**Digital wall thickness testers ULTRA active in box  
incl. external measuring head and calibration plate  
3 ... 300 / 0,01mm IP54**

**Product number:** 2149908

**EAN / GTIN:** 4066918103932

**Customs code:** 90241040

**Delivery method:** Parcel delivery service

**Weight:** 0.25kg



## Product description

- Protection class IP54
- LCD display
- Commutation mm / inch
- Test head with 0,9m cable
- Accuracy:  $\pm 0.5$  % of the measured value
- Ultrasonic pulse echo technique
- Range of sound velocity 1000 to 9999 m/s
- Frequency range 2,5 MHz, test head  $\varnothing$  14mm
- Surface temperature:  $-15^{\circ}\text{C} \dots + 60^{\circ}\text{C}$
- Dust and water proof housing
- Data output RS232

\*\*Delivered in a box incl. probe, zero standard and batteries

### Application:

- Used for measuring thickness corrosion of pressure vessels, chemical equipment, boiler, oil storage tanks, pipes etc.

### Materials:

- Any hard material, like steel, cast iron, aluminium, red copper, brass, zinc, quartz glass, polyethylene, PVC, homogeneous plastics etc.

## Technical Data

**Size:** 3 ... 300 / 0,01mm IP54

**Article number:** 2149908

**Brand:** ULTRA

**Dimension:** 150x74x32mm

**Weight:** 0.25kg