

**Digital pistol grip bore gauge sets, 3-point XT GROOVE
for groove meas., incl. setting rings & UKAS calibration
20-50/0,001/66/80mm Bluetooth**

Product number: 2510603b
Manufacturer number: SP-SXTH5M-BT-GRO
Customs code: 90173000
Delivery method: Parcel delivery service
Weight: 3.6kg



Product description

- DIN 863
- Protection class IP67, Sylvac System
- Stepped hardened steel measuring faces
- Minimum entry-Ø for groove profile: 0.3mm below minimum
- When used with a depth stop, the groove heads can be used to measure plain bores as well as grooves
- Pistol handle
- Large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Constant measuring force, spring loaded

Delivered in a case, including setting rings, UKAS calibration certificate and depth stops

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function \pm
- Max. / min. memory
- Hold function
- Data output Proximity

Contents:

- 1 piece Digital readout unit with pistol grip
- 3 pieces measuring heads (1 piece of each measuring range 20-25 / 25-35 / 35-50mm)
- 2 pieces setting rings (1 piece of each Ø 20mm / 35mm)

! Digital pistol grip bore gauges XT GROOVE for measuring special groove profiles, single devices, tungsten carbide-tipped measuring faces and extensions on request.

! Please specify the dimensions according to the sketch viewable above. This data is required to enable us to prepare a quotation. Alternatively, you can also send us a workpiece drawing.

Technical Data

Size: 20-50/0,001/66/80mm Bluetooth

Article number: 2510603b

Brand: BOWERS

Manufacturer number: SP-SXTH5M-BT-GRO

Accuracy: 0,004mm

Depth stops: Ø 39/45/60mm

For groove depths: 3,175 / 5,5 / 4mm

For groove width: 2mm

Measuring depths: 66/80mm

Measuring force: 35-15N

Measuring range: 20-50mm/.8-2 inch

Reading: 0,001mm/.00005 inch

Setting rings: Ø 20/35mm

Weight: 3.6kg