

## Dial test indicators (Lever type) in box

### Model according to DIN 2270 B

**0,2/0,002/12,8mm Ø32mm**

<b>Product number:</b>	1341105
<b>EAN / GTIN:</b>	4066918047748
<b>Manufacturer number:</b>	K 37
<b>Customs code:</b>	90318020
<b>Delivery method:</b>	Parcel delivery service
<b>Weight:</b>	0.2kg



## Product description

- DIN 2270
- Metal housing
- Turnable outer ring
- Anti-magnetic indicator
- Precision movement in ceramic, ruby or sapphire bearings
- Dovetail slide x3
- Probe swivelling through 240°, carbide ball Ø 2mm, M1.6

**1340 1.. / 1341 1.. / 1342 1..:** Dial test indicators standard

**1340 2..:** Dial test indicators Protection class IP54

**Delivered in a case incl. clamping shaft Ø 8mm and spanner**

## Technical Data

<b>Size:</b>	0,2/0,002/12,8mm Ø32mm
<b>Article number:</b>	1341105
<b>Brand:</b>	KÄFER
<b>Manufacturer number:</b>	K 37
<b>Diameter:</b>	32mm
<b>Execution:</b>	Standard
<b>Measuring range:</b>	0,2mm
<b>Model:</b>	DIN 2270 B
<b>Probe length:</b>	12,8mm
<b>Reading:</b>	0,002mm
<b>Scale:</b>	0-100-0
<b>Weight:</b>	0.2kg