

## Digital external micrometers in box

Tungsten carb. meas. face  $\varnothing$  8mm, pitch 2,0mm, setting gauge

100-130/0,0005mm IP65

**Product number:** 2013105

**EAN / GTIN:** 4066918077585

**Customs code:** 90173000

**Delivery method:** Parcel delivery service

**Weight:** 0.7kg



## Product description

- DIN 863
- Protection class IP65, Sylvac System
- Large LCD display
- Tungsten carbide-tipped measuring faces Ø 8mm
- Non-turning spindle
- Spindle pitch 2.0mm
- Sturdy ratchet with measuring force approximately 7N
- Insulated pads

**Delivered in a case, from 100 - 130mm including setting gauge**

**Functions:**

- On/Off
- mm/inch commutation
- Zero setting at any position
- Reversible reading 0.01/0.001/0.0005mm/.0005"/.00005"/.00002"
- Reversible counting direction
- Preset function
- Max. / min. memory
- Hold function
- Data output Proximity

**! Other types of measuring faces, fittings made of cubic boron nitride (CBN) for measuring faces (increases wear resistance by more than a tenfold), spindle pitch 0.5mm or 1.0mm and sender + receiver for wireless data transmission on [request](#).**

## Technical Data

|                                      |                       |
|--------------------------------------|-----------------------|
| <b>Size:</b>                         | 100-130/0,0005mm IP65 |
| <b>Article number:</b>               | 2013105               |
| <b>Brand:</b>                        | ULTRA                 |
| <b>Data output:</b>                  | Proximity             |
| <b>Insulated pads:</b>               | Yes                   |
| <b>Lifting:</b>                      | Without               |
| <b>Meas. faces tungsten carbide:</b> | Ø 8mm                 |
| <b>Measuring range:</b>              | 100-130mm /4-5 inch   |
| <b>Protection class:</b>             | IP65                  |
| <b>Reading:</b>                      | 0,0005mm/.00002 inch  |
| <b>Weight:</b>                       | 0.7kg                 |