

**Digital wall thickness testers ULTRA active in box  
incl. external measuring head and calibration plate  
1,2 ... 225 / 0,1mm IP54**

**Product number:** 2149905

**EAN / GTIN:** 4066918088314

**Customs code:** 90318080

**Delivery method:** Parcel delivery service

**Weight:** 0.16kg



## Product description

- Protection class IP54
- LCD display
- Commutation mm / inch
- Test head with 1m cable
- Accuracy:  $\pm 0.5$  % of the measured value
- Ultrasonic pulse echo technique
- Range of sound velocity 500 to 9000 m/s
- Frequency range 5 MHz, test head  $\varnothing$  8mm
- Surface temperature:  $-15^{\circ}\text{C} \dots + 60^{\circ}\text{C}$
- Dust and water proof housing
- Data output RS232

\*\*Delivered in a box incl. probe, zero standard and batteries

### Application:

- Used for measuring thickness corrosion of pressure vessels, chemical equipment, boiler, oil storage tanks, pipes etc.

### Materials:

- Any hard material, like steel, cast iron, aluminium, red copper, brass, zinc, quartz glass, polyethylene, PVC, homogeneous plastics etc.

## Technical Data

**Size:** 1,2 ... 225 / 0,1mm IP54

**Article number:** 2149905

**Brand:** ULTRA

**Dimension:** 120x62x30mm

**Weight:** 0.16kg