

**Digital wall thickness testers ULTRA active in box
incl. external measuring head and calibration plate
1,2 ... 225 / 0,1mm IP54**

Product number: 2149905

EAN / GTIN: 4066918088314

Customs code: 90318080

Delivery method: Parcel delivery service

Weight: 0.16kg



Product description

- Protection class IP54
- LCD display
- Commutation mm / inch
- Test head with 1m cable
- Accuracy: ± 0.5 % of the measured value
- Ultrasonic pulse echo technique
- Range of sound velocity 500 to 9000 m/s
- Frequency range 5 MHz, test head \varnothing 8mm
- Surface temperature: $-15^{\circ}\text{C} \dots + 60^{\circ}\text{C}$
- Dust and water proof housing
- Data output RS232

**Delivered in a box incl. probe, zero standard and batteries

Application:

- Used for measuring thickness corrosion of pressure vessels, chemical equipment, boiler, oil storage tanks, pipes etc.

Materials:

- Any hard material, like steel, cast iron, aluminium, red copper, brass, zinc, quartz glass, polyethylene, PVC, homogeneous plastics etc.

Technical Data

Size: 1,2 ... 225 / 0,1mm IP54

Article number: 2149905

Brand: ULTRA

Dimension: 120x62x30mm

Weight: 0.16kg