

**Digital dial test indicators (lever type) S\_Dial TEST Smart  
Bluetooth  
2,0/0,001/36,5mm Ø45mm IP54**

**Product number:** 1339602  
**EAN / GTIN:** 4066918047564  
**Manufacturer number:** 805.4322  
**Customs code:** 90178090  
**Delivery method:** Parcel delivery service  
**Weight:** 0.07kg



## Product description

- Works standard
- Protection class IP54
- LCD display, analogue/digital, turnable 270°
- With Bluetooth function for a wireless data transmission
- Repeatability 0.001mm
- Outer ring Ø 45mm
- Clamping shaft Ø 8mm h6
- Dovetail slide x 3
- Probe swivelling through 270°, tungsten carbide ball Ø 2mm, M 1.4

**Delivered in a cardboard box including manufacturer certificate. Simply scan the QR code on the housing, go to Calibration certificate and save.**

**Functions:**

- On/Off
- Auto-Off
- mm/inch commutation
- Reversible reading 0.01 / 0.001 mm
- Zero setting at any position
- ABS function
- Hold function
- ± Preset function
- MIN. / MAX. / DELTA. memory
- Conversion factor
- Reversible measuring direction
- Key lock
- Data output Proximity

## Technical Data

<b>Size:</b>	2,0/0,001/36,5mm Ø45mm IP54
<b>Article number:</b>	1339602
<b>Brand:</b>	SYLVAC
<b>Manufacturer number:</b>	805.4322
<b>Bluetooth:</b>	With
<b>Error max.:</b>	0,01mm
<b>Measuring force:</b>	0,06N
<b>Measuring range:</b>	2,0mm
<b>Number of probes:</b>	1
<b>Probe length:</b>	36,5mm
<b>Reading:</b>	0,001mm
<b>Weight:</b>	0.07kg