

**Digital hand lever bore gauges 3-point XTL in box
including setting ring and UKAS calibration certificate
65-80/0,001/80mm**

Product number:	2504210
EAN / GTIN:	5051102123840
Manufacturer number:	XTL65M
Customs code:	90173000
Delivery method:	Parcel delivery service
Weight:	4.1kg



Product description

- DIN 863
- Excellent for vertical bore measurement
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Blind bore measurement from 12.5mm
- Movable measuring jaws through hand lever
- Constant measuring force, spring loaded
- Sylvac System, large LCD display
- Self-centering measuring heads for good positive feel

Delivered in a case, including dial gauge, measuring head, setting ring gauge and UKAS calibration certificate

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function \pm
- Max. / min. memory
- Hold function
- Data output Proximity

! Measuring ranges > 100mm, depth extensions and measuring heads with special measuring faces (threads, grooves, spherical, serrations, 2-point etc.), digital dial indicators IP65 and digital dial indicators with bluetooth function for bore gauges > 20mm on request.

Technical Data

Size:	65-80/0,001/80mm
Article number:	2504210
Brand:	BOWERS
Manufacturer number:	XTL65M
Accuracy:	0,005mm
Data output:	Proximity
Measuring depth:	80mm
Measuring force:	35-15N
Measuring range:	65-80mm/2,55-3,15inc
Reading:	0,001mm/.00005 inch
Setting ring:	Ø 65mm
Size A:	0,5mm
Weight:	4.1kg