

Digital external micrometers in box

Tungsten carb. meas. face \varnothing 8mm, pitch 2,0mm, setting gauge

250-280/0,0005mm IP65

Product number: 2013111

EAN / GTIN: 4066918077646

Customs code: 90173000

Delivery method: Parcel delivery service

Weight: 1.73kg



Product description

- DIN 863
- Protection class IP65, Sylvac System
- Large LCD display
- Tungsten carbide-tipped measuring faces Ø 8mm
- Non-turning spindle
- Spindle pitch 2.0mm
- Sturdy ratchet with measuring force approximately 7N
- Insulated pads

Delivered in a case, from 100 - 130mm including setting gauge

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Reversible reading 0.01/0.001/0.0005mm/.0005"/.00005"/.00002"
- Reversible counting direction
- Preset function
- Max. / min. memory
- Hold function
- Data output Proximity

! Other types of measuring faces, fittings made of cubic boron nitride (CBN) for measuring faces (increases wear resistance by more than a tenfold), spindle pitch 0.5mm or 1.0mm and sender + receiver for wireless data transmission on [request](#).

Technical Data

Size:	250-280/0,0005mm IP65
Article number:	2013111
Brand:	ULTRA
Data output:	Proximity
Insulated pads:	Yes
Lifting:	Without
Meas. faces tungsten carbide:	Ø 8mm
Measuring range:	250-280mm / 10-11 in
Protection class:	IP65
Reading:	0,0005mm/.00002 inch
Weight:	1.73kg