

**Digital pistol grip bore gauge sets, 3-point XT GROOVE
for groove meas., incl. setting rings & UKAS calibration
50-100/0,001/80/100mmBluetooth**

Product number: 2510604b
Manufacturer number: SP-SXTH6M-BT-GRO
Customs code: 90173000
Delivery method: Parcel delivery service
Weight: 5.28kg



Product description

- DIN 863
- Protection class IP67, Sylvac System
- Stepped hardened steel measuring faces
- Minimum entry-Ø for groove profile: 0.3mm below minimum
- When used with a depth stop, the groove heads can be used to measure plain bores as well as grooves
- Pistol handle
- Large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Constant measuring force, spring loaded

Delivered in a case, including setting rings, UKAS calibration certificate and depth stops

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function ±
- Max. / min. memory
- Hold function
- Data output Proximity

Contents:

- 1 piece Digital readout unit with pistol grip
- 3 pieces measuring heads (1 piece of each measuring range 50-65 / 65-80 / 80-100mm)
- 2 pieces setting rings (1 piece of each Ø 65mm / 80mm)

! Digital pistol grip bore gauges XT GROOVE for measuring special groove profiles, single devices, tungsten carbide-tipped measuring faces and extensions on request.

! Please specify the dimensions according to the sketch viewable above. This data is required to enable us to prepare a quotation. Alternatively, you can also send us a workpiece drawing.

Technical Data

Size:	50-100/0,001/80/100mmBluetooth
Article number:	2510604b
Brand:	BOWERS
Manufacturer number:	SP-SXTH6M-BT-GRO
Accuracy:	0,005mm
Depth stops:	Ø 80/95/115mm
For groove depths:	8 / 10,5mm
For groove width:	3mm
Measuring depths:	80/100mm
Measuring force:	35-15N
Measuring range:	50-100mm/2-4 inch
Reading:	0,001mm/.00005 inch
Setting rings:	Ø 65/80mm
Weight:	5.28kg