

Product number: 2510604b

# Digital pistol grip bore gauge sets, 3-point XT GROOVE for groove meas., incl. setting rings & UKAS calibration 50-100/0,001/80/100mmBluetooth

**Product number:** 2510604b

Manufacturer number: SP-SXTH6M-BT-GRO

**Customs code:** 90173000

**Delivery method:** Parcel delivery service

Weight: 5.28kg



# Product description

- DIN 863
- Protection class IP67, Sylvac System
- Stepped hardened steel measuring faces
- Minimum entry-Ø for groove profile: 0.3mm below minimum
- When used with a depth stop, the groove heads can be used to measure plain bores as well as grooves
- · Pistol handle
- Large LCD display
- $\bullet \;\;$  With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- · Constant measuring force, spring loaded

# Delivered in a case, including setting rings, UKAS calibration certificate and depth stops

### **Functions:**

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function ±
- Max. / min. memory
- Hold function
- Data output Proximity

### **Contents:**





Product number: 2510604b

- 1 piece Digital readout unit with pistol grip
- 3 pieces measuring heads (1 piece of each measuring range 50-65 / 65-80 / 80-100mm)
- 2 pieces setting rings (1 piece of each Ø 65mm / 80mm)

! Digital pistol grip bore gauges XT GROOVE for measuring special groove profiles, single devices, tungsten carbide-tipped measuring faces and extensions on request.

! Please specify the dimensions according to the sketch viewable above. This data is required to enable us to prepare a quotation. Alternatively, you can also send us a workpiece drawing.

# **Technical Data**

**Size:** 50-100/0,001/80/100mmBluetooth

**Article number:** 2510604b

Brand: BOWERS

Manufacturer number: SP-SXTH6M-BT-GRO

**Accuracy:** 0,005mm

**Depth stops:** Ø 80/95/115mm

**For groove depths:** 8 / 10,5mm

For groove width: 3mm

**Measuring depths:** 80/100mm

Measuring force: 35-15N

**Measuring range:** 50-100mm/2-4 inch

**Reading:** 0,001mm/.00005 inch

**Setting rings:** Ø 65/80mm

Weight: 5.28kg