

**Digital internal micrometer sets in box  
for gear measurements / meas. ends Ø 3mm  
195-600/0,01/0,001/0,0005mm**

**Product number:** 2051502

**EAN / GTIN:** 4066918082794

**Customs code:** 90173000

**Delivery method:** Parcel delivery service

**Weight:** 0.72kg



## Product description

- DIN 863
- Protection class IP65, Sylvac System
- Hardened measuring ends Ø 3x7mm
- Non-turning spindle
- Insulated pads
- Reading 0,01/0,001/0,0005mm - .0005/.00005/.000005 inch

**2051 501:** 195-400mm - approx. 8-16 inch / Extensions: 25mm, 50mm, 100mm

**2051 502:** 195-600mm - approx. 8-24 inch / Extensions: 25mm, 50mm, 100mm, 200mm

**2051 503:** 195-1000mm - approx. 8-40 inch / Extensions: 25mm, 50mm, 100mm, 200mm, 400mm

**2051 504:** 195-1600mm - approx. 8-63 inch / Extensions: 25mm, 50mm, 100mm, 2x 200mm, 2x 400mm

### Delivered in a case

#### Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Reversible reading 0.01 / 0.001mm/0.0005mm
- Reversible counting direction
- ± Preset function
- Max. / min. memory
- Hold function
- Data output Proximity

**! Please order measuring balls in holder No. 2050 4.. separately.**

**! Single extension rods and larger measuring ranges on request.**

## Technical Data

<b>Size:</b>	195-600/0,01/0,001/0,0005mm
<b>Article number:</b>	2051502
<b>Brand:</b>	ULTRA
<b>Measuring force:</b>	7N
<b>Measuring range:</b>	195 - 600mm
<b>Reading:</b>	0,01/0,001/0,0005mm
<b>Spindle pitch:</b>	2mm
<b>Weight:</b>	0.72kg