

**Digital dial indicators S_Dial Work SMART
with LED tolerance signal lights, Bluetooth
25/0,001mm Ø60mm IP54**

Product number:	1301106b
EAN / GTIN:	4066918044631
Manufacturer number:	805.6501
Customs code:	90178090
Delivery method:	Parcel delivery service
Weight:	0.23kg



Product description

- Works standard
- Protection class IP54
- Inductive measuring system
- Large LCD display, turnable up to 270°
- Individually programmable key with required functions
- Repeatability 0.002mm
- Aluminium housing Ø 60mm
- Clamping shaft Ø 8mm h6
- Interchangeable measuring insert M2.5

Delivered in a cardboard box including manufacturer certificate. Simply scan the QR code on the housing, go to Calibration certificate and save.

Functions :

- On/Off
- Auto-Off
- mm/inch commutation
- Zero setting at any position (2 reference points)
- Hold function
- \pm Preset function
- MIN. / MAX. memory
- Conversion factor
- Tolerance signal lights LED red/green/yellow
- Reversible measuring direction
- ABS function
- Key lock
- Data output Proximity

Technical Data

Size:	25/0,001mm Ø60mm IP54
Article number:	1301106b
Brand:	SYLVAC
Manufacturer number:	805.6501
Bluetooth:	With
Error max.:	0,004mm
Measuring force:	0,65-1,15N
Measuring range:	25mm / 1 inch
Reading:	0,001mm / .00005 inc
Weight:	0.23kg