

## Digital internal micrometer sets, 3-point XTD in box including setting rings and UKAS calibration certificate

### 6-10/0,001/58mm Bluetooth

|                             |                         |
|-----------------------------|-------------------------|
| <b>Product number:</b>      | 2502201b                |
| <b>EAN / GTIN:</b>          | 5051102209650           |
| <b>Manufacturer number:</b> | SXTD3M-BT               |
| <b>Customs code:</b>        | 90173000                |
| <b>Delivery method:</b>     | Parcel delivery service |
| <b>Weight:</b>              | 2kg                     |



### Product description

- DIN 863
- Protection class IP67, Sylvac System
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Sturdy ratchet

### Delivered in a case, including setting rings and UKAS calibration certificate

#### Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function  $\pm$
- Max. / min. memory
- Hold function
- Data output Proximity

#### Contents:

- 1 piece Digital readout unit
- 2 pieces measuring heads (1 piece of each measuring range 6-8 / 8-10mm)
- 1 piece setting ring  $\varnothing$  8mm

## Technical Data

|                             |                           |
|-----------------------------|---------------------------|
| <b>Size:</b>                | 6-10/0,001/58mm Bluetooth |
| <b>Article no.:</b>         | 2502201b                  |
| <b>Brand:</b>               | BOWERS                    |
| <b>Manufacturer number:</b> | SXTD3M-BT                 |
| <b>Accuracy:</b>            | 0,004mm                   |
| <b>Data output:</b>         | Proximity                 |
| <b>Measuring depths:</b>    | 58mm                      |
| <b>Measuring force:</b>     | 23-14N                    |
| <b>Measuring range:</b>     | 6-10mm/.25-.4 inch        |
| <b>Protection class:</b>    | IP67                      |
| <b>Reading:</b>             | 0,001mm/.00005 inch       |
| <b>Setting rings:</b>       | Ø 8mm                     |
| <b>Size A:</b>              | 1,6mm                     |
| <b>Weight:</b>              | 2kg                       |