

**Digital internal micrometers sets, 3-point XT500 in box  
including setting ring and calibration certificates  
300-400/0,01/0,001/120mm BT**

**Product number:** 2503201b  
**EAN / GTIN:** 5051102247751  
**Manufacturer number:** SXT3000M-BT  
**Customs code:** 90173000  
**Delivery method:** Parcel delivery service  
**Weight:** 10kg



## Product description

- Works standard
- Protection class IP67, Sylvac System
- Spherical measuring inserts (hardened)
- For through bores only
- Large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Constant measuring force
- Sturdy ratchet

**Delivered in a case, including master reference set 300-325mm, measuring inserts, setting ring Ø 300mm and UKAS calibration certificate**

### Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Reversible reading 0.01 / 0.001mm
- Preset function  $\pm$
- Max. / min. memory
- Hold function
- Data output Proximity

### Application:

- The setting of the instrument will be made by the master reference set (300 – 325mm) and the setting ring gauge Ø 300mm. The other anvil sets are then fitted as required without pre-setting.

**Advantage:**

The setting ring gauge Ø 300mm is sufficient to adjust the instrument within the complete measuring range 300 – 500mm.

**! Measuring depth extensions on request.**

## Technical Data

|                                  |                             |
|----------------------------------|-----------------------------|
| <b>Size:</b>                     | 300-400/0,01/0,001/120mm BT |
| <b>Article no.:</b>              | 2503201b                    |
| <b>Brand:</b>                    | BOWERS                      |
| <b>Manufacturer number:</b>      | SXT3000M-BT                 |
| <b>Accuracy:</b>                 | 0,015mm                     |
| <b>Constant measuring force:</b> | Yes                         |
| <b>Data output:</b>              | Proximity                   |
| <b>Measuring depth:</b>          | 120mm                       |
| <b>Measuring range:</b>          | 300-400mm/12-16 inch        |
| <b>Protection class:</b>         | IP67                        |
| <b>Reading:</b>                  | 0,001mm/.00005 inch         |
| <b>Repeatability:</b>            | 0,003mm                     |
| <b>Setting ring:</b>             | Ø 300mm                     |
| <b>Weight:</b>                   | 10kg                        |