

**Digital hand lever bore gauge sets 3-point XTL in box  
including setting rings and UKAS calibration certificate  
20-50/0,001/66/80mm**

**Product number:** 2504503  
**EAN / GTIN:** 5051102120542  
**Manufacturer number:** SXTL5M  
**Customs code:** 90173000  
**Delivery method:** Parcel delivery service  
**Weight:** 3.43kg



## Product description

- DIN 863
- Excellent for vertical bore measurement
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Blind bore measurement from 12.5mm
- Movable measuring jaws through hand lever
- Constant measuring force, spring loaded
- Sylvac System, large LCD display
- Without Bluetooth function
- Self-centering measuring heads for good positive feel

**Delivered in a case, including dial gauge, measuring heads, setting rings and UKAS calibration certificate**

### Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function  $\pm$
- Max. / min. memory
- Hold function
- Data output Opto

### Contents:

- 1 piece Digital readout unit with dial gauge
- 2 pieces measuring heads (1 piece of each measuring range 6-8 / 8-10mm)
- 1 piece setting ring Ø 8mm

**! Measuring ranges > 100mm, depth extensions and measuring heads with special measuring faces (threads, grooves, spherical, serrations, 2-point etc.), digital dial indicators IP65 and digital dial indicators with bluetooth function for bore gauges > 20mm on request.**

## Technical Data

<b>Size:</b>	20-50/0,001/66/80mm
<b>Article no.:</b>	2504503
<b>Brand:</b>	BOWERS
<b>Manufacturer number:</b>	SXTL5M
<b>Accuracy:</b>	0,004mm
<b>Data output:</b>	Proximity
<b>Measuring depths:</b>	66/80mm
<b>Measuring force:</b>	35-15N
<b>Measuring range:</b>	20-50mm/.8-2 inch
<b>Number of measuring heads:</b>	3
<b>Reading:</b>	0,001mm/.00005 inch
<b>Setting rings:</b>	Ø 20/35mm
<b>Size A:</b>	0,5mm
<b>Weight:</b>	3.43kg