

**Digital pistol grip bore gauge sets, 3-point XT GROOVE
for groove meas., incl. setting rings & UKAS calibration
20-50/0,001/66/80mm Bluetooth**

Product number: 2510603b
Manufacturer number: SP-SXTH5M-BT-GRO
Customs code: 90173000
Delivery method: Parcel delivery service
Weight: 3.6kg



Product description

- DIN 863
- Protection class IP67, Sylvac System
- Stepped hardened steel measuring faces
- Minimum entry-Ø for groove profile: 0.3mm below minimum
- When used with a depth stop, the groove heads can be used to measure plain bores as well as grooves
- Pistol handle
- Large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Constant measuring force, spring loaded

Delivered in a case, including setting rings, UKAS calibration certificate and depth stops

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function ±
- Max. / min. memory
- Hold function
- Data output Proximity

Contents:

- 1 piece Digital readout unit with pistol grip
- 3 pieces measuring heads (1 piece of each measuring range 20-25 / 25-35 / 35-50mm)
- 2 pieces setting rings (1 piece of each Ø 20mm / 35mm)

! Digital pistol grip bore gauges XT GROOVE for measuring special groove profiles, single devices, tungsten carbide-tipped measuring faces and extensions on [request](#).

! Please specify the dimensions according to the sketch viewable above. This data is required to enable us to prepare a quotation. Alternatively, you can also send us a workpiece drawing.

Technical Data

Size:	20-50/0,001/66/80mm Bluetooth
Article no.:	2510603b
Brand:	BOWERS
Manufacturer number:	SP-SXTH5M-BT-GRO
Accuracy:	0,004mm
Depth stops:	Ø 39/45/60mm
For groove depths:	3,175 / 5,5 / 4mm
For groove width:	2mm
Measuring depths:	66/80mm
Measuring force:	35-15N
Measuring range:	20-50mm/.8-2 inch
Reading:	0,001mm/.00005 inch
Setting rings:	Ø 20/35mm
Weight:	3.6kg