

**Digital hand lever bore gauge sets 3-point XTL in box
including setting rings and UKAS calibration certificate
6-10/0,001/58mm Bluetooth**

Product number: 2504501b
EAN / GTIN: 5051102251505
Manufacturer number: SXTL3M-BT
Customs code: 90173000
Delivery method: Parcel delivery service
Weight: 2.28kg



Product description

- DIN 863
- Protection class IP67, Sylvac System
- Excellent for vertical bore measurement
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Blind bore measurement from 12.5mm
- Movable measuring jaws through hand lever
- Constant measuring force, spring loaded
- Sylvac System, large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Self-centering measuring heads for good positive feel

Delivered in a case, including dial gauge, measuring heads, setting rings and UKAS calibration certificate

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function \pm
- Max. / min. memory
- Hold function
- Data output Proximity

Contents:

- 1 piece Digital readout unit with dial gauge
- 2 pieces measuring heads (1 piece of each measuring range 6-8 / 8-10mm)
- 1 piece setting ring Ø 8mm

! Measuring ranges > 100mm, depth extensions and measuring heads with special measuring faces (threads, grooves, spherical, serrations, 2-point etc.), digital dial indicators IP65 and digital dial indicators with bluetooth function for bore gauges > 20mm on request.

Technical Data

Size:	6-10/0,001/58mm Bluetooth
Article no.:	2504501b
Brand:	BOWERS
Manufacturer number:	SXTL3M-BT
Accuracy:	0,004mm
Data output:	Proximity
Measuring depths:	58mm
Measuring force:	18-8N
Measuring range:	6-10mm/.25-.4 inch
Number of measuring heads:	2
Reading:	0,001mm/.00005 inch
Setting rings:	Ø 8mm
Size A:	1,6mm
Weight:	2.28kg