

**Digital dial indicators S\_Dial Work SMART  
with LED tolerance signal lights, Bluetooth  
50/0,001mm Ø60mm IP54**

**Product number:** 1301107b  
**EAN / GTIN:** 4066918044655  
**Manufacturer number:** 805.6621  
**Customs code:** 90178090  
**Delivery method:** Parcel delivery service  
**Weight:** 0.25kg



## Product description

- Works standard
- Protection class IP54
- Inductive measuring system
- Large LCD display, turnable up to 270°
- Individually programmable key with required functions
- Repeatability 0.002mm
- Aluminium housing Ø 60mm
- Clamping shaft Ø 8mm h6
- Interchangeable measuring insert M2.5

**Delivered in a cardboard box including manufacturer certificate. Simply scan the QR code on the housing, go to Calibration certificate and save.**

**Functions :**

- On/Off
- Auto-Off
- mm/inch commutation
- Zero setting at any position (2 reference points)
- Hold function
- $\pm$  Preset function
- MIN. / MAX. memory
- Conversion factor
- Tolerance signal lights LED red/green/yellow
- Reversible measuring direction
- ABS function
- Key lock
- Data output Proximity

## Technical Data

|                             |                       |
|-----------------------------|-----------------------|
| <b>Size:</b>                | 50/0,001mm Ø60mm IP54 |
| <b>Article number:</b>      | 1301107b              |
| <b>Brand:</b>               | SYLVAC                |
| <b>Manufacturer number:</b> | 805.6621              |
| <b>Bluetooth:</b>           | With                  |
| <b>Error max.:</b>          | 0,005mm               |
| <b>Measuring force:</b>     | 1,4-2,9N              |
| <b>Measuring range:</b>     | 50mm / 2 inch         |
| <b>Reading:</b>             | 0,001mm / .00005 inc  |
| <b>Weight:</b>              | 0.25kg                |