

**Digital dial test indicators (lever type) S\_Dial TEST Smart**  
**Bluetooth**  
**0,8/0,001/12,5mm Ø45mm IP54**

**Product number:** 1339601  
**EAN / GTIN:** 4066918047557  
**Manufacturer number:** 805.4321  
**Customs code:** 90178090  
**Delivery method:** Parcel delivery service  
**Weight:** 0.07kg



### Product description

- Works standard
- Protection class IP54
- LCD display, analogue/digital, turnable 270°
- With Bluetooth function for a wireless data transmission
- Repeatability 0.001mm
- Outer ring Ø 45mm
- Clamping shaft Ø 8mm h6
- Dovetail slide x 3
- Probe swivelling through 270°, tungsten carbide ball Ø 2mm, M 1.4

**Delivered in a cardboard box including manufacturer certificate. Simply scan the QR code on the housing, go to Calibration certificate and save.**

**Functions:**

- On/Off
- Auto-Off
- mm/inch commutation
- Reversible reading 0.01 / 0.001mm
- Zero setting at any position
- ABS function
- Hold function
- $\pm$  Preset function
- MIN. / MAX. / DELTA. memory
- Conversion factor
- Reversible measuring direction
- Key lock
- Data output Proximity

## Technical Data

|                             |                             |
|-----------------------------|-----------------------------|
| <b>Size:</b>                | 0,8/0,001/12,5mm Ø45mm IP54 |
| <b>Article number:</b>      | 1339601                     |
| <b>Brand:</b>               | SYLVAC                      |
| <b>Manufacturer number:</b> | 805.4321                    |
| <b>Bluetooth:</b>           | With                        |
| <b>Error max.:</b>          | 0,004mm                     |
| <b>Measuring force:</b>     | 0,15N                       |
| <b>Measuring range:</b>     | 0,8mm                       |
| <b>Number of probes:</b>    | 1                           |
| <b>Probe length:</b>        | 12,5mm                      |
| <b>Reading:</b>             | 0,001mm                     |
| <b>Weight:</b>              | 0.07kg                      |