

**Digital hand lever bore gauges 3-point XTL in box
including setting ring and UKAS calibration certificate
25-35/0,001/66mm**

Product number: 2504207
EAN / GTIN: 5051102123819
Manufacturer number: XTL25M
Customs code: 90173000
Delivery method: Parcel delivery service
Weight: 2.6kg



Product description

- DIN 863
- Excellent for vertical bore measurement
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Blind bore measurement from 12.5mm
- Movable measuring jaws through hand lever
- Constant measuring force, spring loaded
- Sylvac System, large LCD display
- Self-centering measuring heads for good positive feel

Delivered in a case, including dial gauge, measuring head, setting ring gauge and UKAS calibration certificate

Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function \pm
- Max. / min. memory
- Hold function
- Data output Proximity

! Measuring ranges > 100mm, depth extensions and measuring heads with special measuring faces (threads, grooves, spherical, serrations, 2-point etc.), digital dial indicators IP65 and digital dial indicators with bluetooth function for bore gauges > 20mm on request.

Technical Data

Size:	25-35/0,001/66mm
Article number:	2504207
Brand:	BOWERS
Manufacturer number:	XTL25M
Accuracy:	0,004mm
Data output:	Proximity
Measuring depth:	66mm
Measuring force:	35-15N
Measuring range:	25-35mm/1-1.37 inch
Reading:	0,001mm/.00005 inch
Setting ring:	Ø 35mm
Size A:	0,5mm
Weight:	2.6kg