

## Dial test indicators (Lever type) in box

### Model according to DIN 2270 A

### 0,2/0,002/12,8mm Ø40mm

|                             |                         |
|-----------------------------|-------------------------|
| <b>Product number:</b>      | 1340106                 |
| <b>EAN / GTIN:</b>          | 4066918047656           |
| <b>Manufacturer number:</b> | K 46                    |
| <b>Customs code:</b>        | 90318020                |
| <b>Delivery method:</b>     | Parcel delivery service |
| <b>Weight:</b>              | 0.2kg                   |



## Product description

- DIN 2270
- Metal housing
- Turnable outer ring
- Anti-magnetic indicator
- Precision movement in ceramic, ruby or sapphire bearings
- Dovetail slide x3
- Probe swivelling through 240°, carbide ball Ø 2mm, M1.6

**1340 1.. / 1341 1.. / 1342 1..:** Dial test indicators standard

**1340 2..:** Dial test indicators Protection class IP54

**Delivered in a case incl. clamping shaft Ø 8mm and spanner**

## Technical Data

|                             |                        |
|-----------------------------|------------------------|
| <b>Size:</b>                | 0,2/0,002/12,8mm Ø40mm |
| <b>Article number:</b>      | 1340106                |
| <b>Brand:</b>               | KÄFER                  |
| <b>Manufacturer number:</b> | K 46                   |
| <b>Diameter:</b>            | 40mm                   |
| <b>Execution:</b>           | Standard               |
| <b>Measuring range:</b>     | 0,2mm                  |
| <b>Model:</b>               | DIN 2270 A             |
| <b>Probe length:</b>        | 12,8mm                 |
| <b>Reading:</b>             | 0,002mm                |
| <b>Scale:</b>               | 0-100-0                |
| <b>Weight:</b>              | 0.2kg                  |