

**Digital dial indicators S\_Dial Work SMART  
with LED tolerance signal lights, Bluetooth  
12,5/0,001mm Ø60mm IP54**

<b>Product number:</b>	1301105b
<b>EAN / GTIN:</b>	4066918044617
<b>Manufacturer number:</b>	805.6301
<b>Customs code:</b>	90178090
<b>Delivery method:</b>	Parcel delivery service
<b>Weight:</b>	0.21kg



## Product description

- Works standard
- Protection class IP54
- Inductive measuring system
- Large LCD display, turnable up to 270°
- Individually programmable key with required functions
- Repeatability 0.002mm
- Aluminium housing Ø 60mm
- Clamping shaft Ø 8mm h6
- Interchangeable measuring insert M2.5

**Delivered in a cardboard box including manufacturer certificate. Simply scan the QR code on the housing, go to Calibration certificate and save.**

**Functions :**

- On/Off
- Auto-Off
- mm/inch commutation
- Zero setting at any position (2 reference points)
- Hold function
- $\pm$  Preset function
- MIN. / MAX. memory
- Conversion factor
- Tolerance signal lights LED red/green/yellow
- Reversible measuring direction
- ABS function
- Key lock
- Data output Proximity

## Technical Data

<b>Size:</b>	12,5/0,001mm Ø60mm IP54
<b>Article number:</b>	1301105b
<b>Brand:</b>	SYLVAC
<b>Manufacturer number:</b>	805.6301
<b>Bluetooth:</b>	With
<b>Error max.:</b>	0,003mm
<b>Measuring force:</b>	0,65-0,9N
<b>Measuring range:</b>	12,5mm / .5 inch
<b>Reading:</b>	0,001mm / .00005 inc
<b>Weight:</b>	0.21kg