

**Digital internal micrometers, 3-point XTD in box  
including setting ring and UKAS calibration certificate  
200-225/0,001/118mm Bluetooth**

|                             |                         |
|-----------------------------|-------------------------|
| <b>Product number:</b>      | 2502120b                |
| <b>EAN / GTIN:</b>          | 5051102210090           |
| <b>Manufacturer number:</b> | XTD200M-BT              |
| <b>Customs code:</b>        | 90173000                |
| <b>Delivery method:</b>     | Parcel delivery service |
| <b>Weight:</b>              | 3.8kg                   |



## Product description

- DIN 863
- Protection class IP67, Sylvac System
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Sturdy ratchet

**Delivered in a case, including setting ring and UKAS calibration certificate**

### Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function  $\pm$
- Max. / min. memory
- Hold function
- Data output Proximity

## Technical Data

|                             |                               |
|-----------------------------|-------------------------------|
| <b>Size:</b>                | 200-225/0,001/118mm Bluetooth |
| <b>Article number:</b>      | 2502120b                      |
| <b>Brand:</b>               | BOWERS                        |
| <b>Manufacturer number:</b> | XTD200M-BT                    |
| <b>Accuracy:</b>            | 0,008mm                       |
| <b>Data output:</b>         | Proximity                     |
| <b>Measuring depth:</b>     | 118mm                         |
| <b>Measuring force:</b>     | 62-47N                        |
| <b>Measuring range:</b>     | 200-225mm/8-9 inch            |
| <b>Protection class:</b>    | IP67                          |
| <b>Reading:</b>             | 0,001mm/.00005 inch           |
| <b>Setting ring:</b>        | With                          |
| <b>Setting ring:</b>        | Ø 225mm                       |
| <b>Size A:</b>              | 0,5mm                         |
| <b>Weight:</b>              | 3.8kg                         |