

## Dial test indicators (Lever type) in box

### Model according to DIN 2270 C

0,2/0,002/12,8mm Ø32mm

**Product number:** 1342105  
**EAN / GTIN:** 4066918047809  
**Manufacturer number:** K 38  
**Customs code:** 90318020  
**Delivery method:** Parcel delivery service  
**Weight:** 0.2kg



## Product description

- DIN 2270
- Metal housing
- Turnable outer ring
- Anti-magnetic indicator
- Precision movement in ceramic, ruby or sapphire bearings
- Dovetail slide x3
- Probe swivelling through 240°, carbide ball Ø 2mm, M1.6

**1340 1.. / 1341 1.. / 1342 1..:** Dial test indicators standard

**1340 2..:** Dial test indicators Protection class IP54

**Delivered in a case incl. clamping shaft Ø 8mm and spanner**

## Technical Data

|                             |                        |
|-----------------------------|------------------------|
| <b>Size:</b>                | 0,2/0,002/12,8mm Ø32mm |
| <b>Article number:</b>      | 1342105                |
| <b>Brand:</b>               | KÄFER                  |
| <b>Manufacturer number:</b> | K 38                   |
| <b>Diameter:</b>            | 32mm                   |
| <b>Execution:</b>           | Standard               |
| <b>Measuring range:</b>     | 0,2mm                  |
| <b>Model:</b>               | DIN 2270 C             |
| <b>Probe length:</b>        | 12,8mm                 |
| <b>Reading:</b>             | 0,002mm                |
| <b>Scale:</b>               | 0-100-0                |
| <b>Weight:</b>              | 0.2kg                  |