

**Internal micrometers, 3-point XTA in box  
including setting ring and UKAS calibration certificate  
20-25/0,005/66mm**

<b>Product number:</b>	2095107
<b>EAN / GTIN:</b>	5051102049010
<b>Manufacturer number:</b>	XTA20M
<b>Customs code:</b>	90173000
<b>Delivery method:</b>	Parcel delivery service
<b>Weight:</b>	0.5kg



## Product description

- DIN 863
- Satin chrome reading parts
- For measuring ranges < 20mm XTA MICRO will be delivered
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Spindle pitch 0.5mm
- Sturdy ratchet

**Delivered in a case, including setting ring and UKAS calibration certificate**

## Technical Data

<b>Size:</b>	20-25/0,005/66mm
<b>Article number:</b>	2095107
<b>Brand:</b>	BOWERS
<b>Manufacturer number:</b>	XTA20M
<b>Accuracy:</b>	0,004mm
<b>Measuring depth:</b>	66mm
<b>Measuring force:</b>	29-15N
<b>Measuring range:</b>	20-25mm
<b>Reading:</b>	0,005mm
<b>Reading parts:</b>	Satin chrome plated
<b>Setting ring:</b>	With
<b>Setting ring:</b>	Ø 20mm
<b>Size A:</b>	0,5mm
<b>Spindle pitch:</b>	0,5mm
<b>Weight:</b>	0.5kg