

**Digital pistol grip bore gauge sets, 3-point XTH in box including setting rings and UKAS calibration certificate**  
**6-20/0,001/58/62mm Bluetooth**

|                             |                         |
|-----------------------------|-------------------------|
| <b>Product number:</b>      | 2510507b                |
| <b>EAN / GTIN:</b>          | 5051102207427           |
| <b>Manufacturer number:</b> | SXTH10M-BT              |
| <b>Customs code:</b>        | 90173000                |
| <b>Delivery method:</b>     | Parcel delivery service |
| <b>Weight:</b>              | 2.7kg                   |



## Product description

- DIN 863
- Protection class IP67, Sylvac System
- Tungsten carbide-tipped measuring faces (< 12.5mm with steel measuring faces hardened)
- Pistol handle
- Large LCD display
- With Bluetooth function and SylvacBT Smart App for a wireless data transmission
- Constant measuring force, spring loaded

### Delivered in a case, including setting rings and UKAS calibration certificate

#### Functions:

- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function  $\pm$
- Max. / min. memory
- Hold function
- Data output Proximity

#### Contents:

- 1 piece Digital readout unit with pistol grip
- 5 pieces measuring heads (1 piece of each measuring range 6-8 / 8-10 / 10-12.5 / 12.5-16 / 16-20mm)
- 3 pieces setting rings (1 piece of each  $\varnothing$  8 / 12.5 / 20mm)

## Technical Data

|                             |                              |
|-----------------------------|------------------------------|
| <b>Size:</b>                | 6-20/0,001/58/62mm Bluetooth |
| <b>Article number:</b>      | 2510507b                     |
| <b>Brand:</b>               | BOWERS                       |
| <b>Manufacturer number:</b> | SXTH10M-BT                   |
| <b>Accuracy:</b>            | 0,004mm                      |
| <b>Data output:</b>         | Proximity                    |
| <b>Measuring depths:</b>    | 58/62mm                      |
| <b>Measuring force:</b>     | 18-8N                        |
| <b>Measuring range:</b>     | 6-20mm/.25-.8 inch           |
| <b>Protection class:</b>    | IP67                         |
| <b>Reading:</b>             | 0,001mm/.00005 inch          |
| <b>Setting rings:</b>       | Ø 8/12,5/20mm                |
| <b>Size A:</b>              | 1,6/1,9/0,5mm                |
| <b>Weight:</b>              | 2.7kg                        |